

Technische Angaben/ Technical data	Mini Sender
Videoeingang / <i>Video input</i>	FBAS- oder BAS-Normsignal, pos. 1 + 0.1 V _{ss} an 75 Ohm / <i>composite colour picture signal or picture blanking synchronous signal, pos. 1 ± 0.1 V_{pp}</i>
Videobandbreite / <i>Video bandwidth</i>	30 Hz - 7 MHz
Modulationsart / <i>Modulation mode</i>	F3F (Video/ Audio frequenzmoduliert)
Stromversorgung / <i>Power supply DC</i>	12 V + 0.5 V
Stromaufnahme ca. / <i>Current consumption</i>	130 mA
Antenne / <i>Antenna</i>	10 mW, 25 mW, 80 mW - Rundstrahlantenne / <i>omnidirectional antenna</i> 80 mW - SMA Buchse / <i>SMA female</i> 160 mW Platine / <i>PCB</i>
Abmessungen mm ohne Antenne / <i>Dimensions without antenna</i>	54 x 54 x 34
Gewicht ca / <i>Weight</i>	80 g
Schutzgrad / <i>Protection class</i>	IP 30
Temperaturbereiche (Betrieb/ Lagerung) / <i>Ambient temperatures (use/ store)</i>	-10°C- +55°C / -20°C- +60°C
Luftfeuchtigkeit / <i>Humidity</i>	max. 70% nicht kondensierend / <i>non- condensing</i>
Anschlüsse / Connectors	
Videoeingang / <i>Video input</i>	Cinch / <i>RCA</i>
DC	2.1 / 5.5 mm